

Eaton 5P UPS

650 - 1550VA



Superior manageability and energy metering capabilities for better IT decision-making

Manageability

- The graphical LCD display provides clear information on the UPS's status and measurements on a single screen (in seven languages). Enhanced configuration capabilities are also available with easy-to-use navigation keys.
- **Meters energy consumption** and provides kWh values through the LCD and Intelligent Power® Software.
- Load segment control enables prioritised shutdowns of nonessential equipment to maximise battery runtime for critical devices. Load segment control can also be used to remotely reboot locked-up network equipment or to manage scheduled shutdowns and sequential start-ups.
- The 5P offers Serial and USB connectivity, plus an extra slot for an optional communication card (including SNMP/Web card or relay contact card). Eaton's Intelligent Power® Software Suite compatible with all major OS including virtualization software such as VMware and Hyper-V is included with each UPS.

Performance and Efficiency

- With an optimised electrical design, the 5P can provide up to 98% efficiency, contributing to lower cooling and utility costs.

Pure sinewave output

- When operating in battery mode the 5P provides a high quality output signal for any sensitive equipment connected, such as active PFC (power factor corrected) servers.

Availability and Flexibility

- 5P is available as a tower or rack form factor to cater for varied deployment applications.
- Stronger, longer battery life: Eaton ABM® battery management technology uses an innovative three-stage charging technique that only recharges the battery when necessary, so the battery experiences less corrosion and service life is prolonged by up to 50%.
- Batteries can be hot-swapped without ever having to shut down connected equipment. With an optional, hot-swap maintenance bypass module, you can even replace the entire UPS.

Ideal for protecting:

- Servers
- Switches
- Routers
- Storage devices



Tower or Rack form factor



Intuitive LCD display for ease of configuration and management



Eaton 5P 1550 tower and rack

What's in the box:

Tower:

- 5P Tower UPS
- Quick Start guide & safety instructions
- User manual and software suite CD
- RS232 & USB communications cables

What's in the box:

Rack:

- 5P 1RU Rack UPS
- Quick Start guide & safety instructions
- User manual and software suite CD
- RS232 & USB communications cables
- 2 x output IEC (10A) cables
- Output cables retention bracket
- 1RU rack kit (ears only for 650VA)



1. Communications card slot
2. Remotely switchable outlet groups
3. Remote On/Off, Remote Power Off terminal
4. USB Port
5. Serial Port
6. Primary outlet group



Technical Specifications	650	850	1150	1550
Rating (VA/W)	650VA/420W	850VA/600W	1150VA/770W	1550VA/1100W
Format	Tower or 1RU Rack			
Electrical characteristics				
Technology	Line-Interactive High Frequency (Pure Sinewave, Booster + Fader)			
Input voltage and frequency ranges without using batteries	160V-294V (adjustable to 150V-294V) 47 to 70 Hz (50 Hz system), 56.5 to 70 Hz (60 Hz system), 40 Hz in low-sensitivity mode			
Output voltage and frequency	230 V (+6/-10 %) (Adjustable to 200V / 208V / 220V / 230V / 240V), 50/60 Hz +/- 0.1 % (autosensing)			
Connections				
Input	Tower: Fixed line cord 10A AU 1.8mtr Rack: IEC C14 (10A) socket	Tower: Fixed line cord 10A AU 1.8mtr Rack: IEC C14 (10A) socket	Tower: Fixed line cord 10A AU 1.8mtr Rack: IEC C14 (10A) socket	Tower: Fixed line cord 10A AU 1.8mtr Rack: IEC C14 (10A) socket
Outputs	Tower: 2 x AU 10A, 3 x IEC C13 (10A) Rack: 4 x IEC C13 (10A)	Tower: 2 x AU 10A, 3 x IEC C13 (10A) Rack: 4 x IEC C13 (10A)	Tower: 2 x AU 10A, 3 x IEC C13 (10A) Rack: 6 x IEC C13 (10A)	Tower: 2 x AU 10A, 3 x IEC C13 (10A) Rack: 6 x IEC C13 (10A)
Remotely controlled sockets	Tower: 2 x 10A AU individually switched Rack: 2 x IEC C13 (10A) individually switched	Tower: 2 x 10A AU individually switched Rack: 2 x IEC C13 (10A) individually switched	Tower: 2 x 10A AU individually switched Rack: 3 x IEC C13 (10A), grouped 2+1 switched	Tower: 2 x 10A AU individually switched Rack: 3 x IEC C13 (10A), grouped 2+1 switched
Batteries Typical backup times for 50 and 70% load*				
5P	9/5.5 mins	12/7.5 mins	12/7.5 mins	13/8.5 mins
Battery management	ABM® & Temperature compensated charging method (user selectable), Automatic battery test, deep discharge protection, to automatic recognition of external battery units.			
Interfaces				
Communication ports	1 USB port + 1 RS232 serial port and relay contacts (USB and RS232 ports cannot be used simultaneously) + 1 mini terminal block for remote ON/OFF or Remote Power Off			
Communications card slots	1 slot for NETWORK-MS, MODBUS-MS or RELAY-MS cards			
Operating conditions, standards and approvals				
Operating temperature	Models 650, 850 & 1550 = "0-35°C", Model 1550 = "0-40°C"			
Noise Level	< 40dBA			
Performance - Safety - EMC	IEC/EN 62040-1-1 (Safety), IEC/EN 62040-2 (EMC), IEC/EN 62040-3 (Performance), C-Tick			
Approvals	CE, CB report, TÜV			
Dimensions W x D x H / Weight				
UPS Dimensions (mm) & weight (kg)-Tower	150 x 345 x 230mm / 7.8kg	150 x 345 x 230mm / 10.4kg	150 x 345 x 230mm / 11.1kg	150 x 445 x 230mm / 15.6kg
UPS Dimensions (mm) & weight (kg) - Rack	438 x 364 x 43.2mm(1RU) / 8.6kg	438 x 509 x 43.2mm(1RU) / 13.8kg	438 x 509 x 43.2mm(1RU) / 14.6kg	438 x 554 x 43.2mm(1RU) / 19.4kg
Customer Service & Support				
Warranty	3 years on electronics, 2 years on batteries			
Part Numbers				
5P Tower	5P650AU	5P850AU	5P1150AU	5P1550AU
5P Rack	5P650iR	5P850iR	5P1150iR	5P1550iR

* Runtimes are shown at 0.7 power factor. Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.



Powering Business Worldwide

www.poweronaustralia.com.au

Power On Australia Pty Ltd | ABN 48 110 752 442 | PH 1300 662 435 | FX 1300 76 24 16
sales@poweronaustralia.com.au